Dunn-Edwards PAINTS

THE #1 CHOICE OF PAINTING PROFESSIONALS®

SUPREMA®
Interior Velvet Paint
SPMA20-1

RAVOC RATED ACRYLIC™ | Contains no Ethylene Glycol or other Toxic Air Contaminants EG-FREE® | MILDEW RESISTANT | CERTIFIED BY green wise® COATINGS RESEARCH GROUP, INCORPORATED

DESCRIPTION: SUPREMA® Velvet is an ultra-premium interior, ultra-low VOC, acrylic latex velvet paint that combines exceptional hide with superior stain resistance and washability. **SUPREMA Velvet** provides long-lasting protection, applies easily, dries quickly and has low odor. It is ideal for high-end residential and commercial projects, such as schools and hospitals, where self-priming, ultra-low VOC products are preferred.

PRODUCT INFORMATION

SOLVENT TYPE: Waterborne | **RESIN TYPE:** Acrylic copolymer

FINISH (ASTM D 523)**:** Velvet: 5–9% on a 60° meter; 10–15% on an 85° meter

TINT BASES: L Tintable White, M Medium, U Ultra Deep

VISCOSITY@77°F/25°C (ASTM D 562)**:** 100–106 KU

MAXIMUM VOC CONTENT
50 g/L (as supplied)

MAXIMUM RAVOC (Reactivity-Adjusted VOC)
25 g/L

SOLIDS BY VOLUME (ASTM D 2697)
40.0% ± 2%

SOLIDS BY WEIGHT
54.0% ± 2%

WEIGHT PER GALLON (ASTM D 1475)**:** 11.10 lbs.

COMPOSITION BY WEIGHT

Pigment–34.1%		**Vehicle–65.9%**	
*Prime pigments	19.4	Vinyl acrylics	18.5
Reinforcing pigments	14.7	Water & additives	47.4

**Prime pigments include titanium dioxide (TiO_2), plus all other pigments directly adding to the hiding power of this paint.*

RECOMMENDED FILM THICKNESS PER COAT
Wet: 3.8 mils Dry: 1.5 mils

PRACTICAL COVERAGE PER COAT AT RECOMMENDED DRY FILM THICKNESS
Approximately 375–425 sq. ft. per gallon, depending on surface conditions and application techniques.

THINNING RECOMMENDATION: This coating is intended to be applied without thinning or diluting under normal environmental and application conditions. If necessary to maintain good workability, add up to 1/4 pint (4 fl. oz.) of clean water per gallon of coating.

AVERAGE DRY TIME@77°F/25°C (ASTM D 1640)
To touch: 1–2 hours Recoat: 4–6 hours
Dry times and recoat times are temperature, humidty and film thickness dependent.

APPLICATION EQUIPMENT: Brush, roller, airless spray

PACKAGING: Quart, one-gallon, five-gallon containers

STORAGE: Store in a dry area. Protect from freezing. Protect from temperatures above 110°F for extended periods of time. Extreme temperatures may cause paint to become unusable. See ***Paint Storage Best Practices*** Technical Bulletin at dunnedwards.com for more information.

CLEANUP: Warm, soapy water

DISPOSAL: For information on local options to dispose of unwanted leftover paint, call Dunn-Edwards Customer Service at 1-888-DEPAINT or visit www.dunnedwards.com. **Do not mix with other products**.

CONFORMS TO: ARB 2007 SCM & CALGreen 2013; LEED 2009 IEQ Credit 4.2; MPI Approved Product #138; CRGI Green Wise Certified; FDA Guidelines for Resinous & Polymeric Coatings

SAFETY DATA SHEET: Available at www.dunnedwards.com

SURFACE PREPARATION: All surfaces must be cured, clean, dry, and free from dirt, dust, rust, stains, grease, oil, mildew, wax, efflorescence, bond-breakers, and other contaminants. Remove all loose, peeling, or chalky paint by sanding, scraping, or other appropriate methods. Repair all cracks, holes, and other surface imperfections with a suitable patching material. Repaired surfaces should then be sanded smooth and dusted clean. Glossy surfaces should be dulled to provide a roughened surface for good adhesion.

SURFACE PREPARATION: SUPREMA Velvet is self priming on most surfaces. For previously painted surfaces that are properly repaired as needed, one (1) coat may be sufficient. For properly prepared new surfaces, two (2) coats are typically required. All surfaces must be cured, clean, dry, and free from dirt, dust, rust, stains, grease, oil, mildew, wax, efflorescence, bond-breakers, and other contaminants. Remove all loose, peeling, or chalky paint by sanding, scraping, or other appropriate methods. Repair all cracks, holes, and other surface imperfections with a suitable patching material. Repaired surfaces should then be sanded smooth and dusted clean. Glossy surfaces should be dulled to provide a roughened surface for good adhesion.

SPECIAL INSTRUCTIONS

- CAUTION: Scraping or sanding surfaces of older buildings (especially pre-1978) may release dust containing lead or asbestos. EXPOSURE TO LEAD OR ASBESTOS CAN BE VERY HAZARDOUS TO YOUR HEALTH. Always wear appropriate personal protective equipment during surface preparation, and finish cleanup of any residues by water-washing all surfaces. For more information, see Dunn-Edwards brochure on "Surface Preparation Safety" or call EPA's National Lead Information Hotline at 1-800-424-LEAD, or visit www.epa.gov/lead or /asbestos, or contact your state or local Health Department.
- This product can neither cause nor prevent or cure the growth of mold, mildew, or other forms of fungus. Excessive moisture and inadequate ventilation are the main conditions that promote their growth. Correct any such conditions before painting.
- On Level 4 and 5 Drywall Finishes, use **VINYLASTIC Plus** thinned with 10% of clean water (3/4 pints per gallon or 1/2 gallon per 5-gallons) for best penetration.
- Do not apply when the air or surface temperature is below 50°F.

PRIMERS

DRYWALL
Textured: **VINYLASTIC® Premium (VNPR00)**
Untextured: **VINYLASTIC® Premium (VNPR00)**
Skim-coated: **VINYLASTIC® Plus (VNPL00)**

MASONRY
Plaster:
Tilt-up concrete:
Poured-in-place:
Brick:
Concrete block:
Smooth trowel:
} **EFF-STOP® Premium (ESPR00)**

WOOD
Doors, trim: **INTERKOTE® Premium (IKPR00)**

SYNTHETIC WOOD
Masonite:
Hardboard:
INTERKOTE® Premium (IKPR00)

METAL
Ferrous: **BLOC-RUST® Premium (BRPR00)**, **ULTRASHIELD® Galvanized Metal Primer (ULGM00)** or **ULTRA-GRIP® Premium (UGPR00)**
Non-ferrous[1]: **ULTRASHIELD® Galvanized Metal Primer (ULGM00)** or **ULTRA-GRIP® Premium (UGPR00)**

[1]These surfaces require special primers that will create noticeable odor.

DUNN-EDWARDS CORPORATION • 4885 East 52ND Place • Los Angeles, California 90058-5507 • (888) DE PAINT | dunnedwards.com
337-2468